

Hamamatsu Deuterium Lamps

Part Number	Guaranteed	Window Material	Min		Aperture		Filament	Warm Up	Filament	Operating
	Life hours		nm	nm	Dia. Size mm	Fluctuation % p-p	Warm Up Vdc	Variation ±Vdc	Operating Vdc	variation ±Vdc
L1314		Synthetic Silica	160	400	2.5	0.5	10	1	5	
L1835		MgF2	115	400	2.5	0.5	10	1	5	
L6301	2000	UV Glass	185	400	0.5	0.05	2	0.25	1	0.1
L6302	2000	UV Glass	185	400	1	0.05	2.5	0.25	1	0.1
L6303	2000	UV Glass	185	400	0.5	0.05	2.5	0.25	1.7	0.2
L6304	2000	UV Glass	185	400	1	0.05	2.5	0.25	1.7	0.2
L6305	2000	UV Glass	185	400	0.5	0.05	3	0.3		
L6306	2000	UV Glass	185	400	1	0.05	3	0.3		
L6307	2000	UV Glass	185	400	0.5	0.05	10	1		
L6308	2000	UV Glass	185	400	1	0.05	10	1		
L6309	2000	UV Glass	185	400	0.5	0.005	10	1	7	0.5
L6310	2000	UV Glass	185	400	1	0.005	10	1	7	0.5
L6311	2000	UV Glass	185	400	0.5	0.005	13	1	0	0
L6311-50	2000	UV Glass	185	400	0.5	0.05			0	
L6312	2000	UV Glass	185	400	1	0.005	13	1	0	0
L6312-50	2000	UV Glass	185	400	1	0.005	13	1	0	0
L6565	4000	UV Glass	185	400	1	0.005	2.5	0.25	1	0.1
L6566	4000	UV Glass	185	400	1	0.05	3	0.3	1	0
L6999	2000	UV Glass	185	400	0.5	0.05	2.5	0.25	1	0.1
L6999-50	2000	UV Glass	185	400	0.5	0.05	2.5	0.25	1	0.1
L6999-51	2000	UV Glass	185	400	0.5	0.05	2.5	0.25	1	0.1
L7174	2000	UV Glass	185	400	1	0.05	2.5	0.25	1	0.1
L7292	2000	MgF2	115	400	1	-	10	1	2.5	
L7293	2000	MgF2	115	400	1	-	2.5	0.25	1	0.1
L7295	2000	Synthetic Silica	160	400	1	0.05	10	1	7	0.5
L7296	2000	Synthetic Silica	160	400	0.5	0.05	10	1	7	0.5
L7296-50	2000	Synthetic Silica	160	400	0.5	0.05	10	1	7	0.5
L7298	2000	Synthetic Silica	160	400	1	0.05	2.5	0.25	1.7	0.2
L7306	2000	UV Glass	185	400	1	0.05	2.5	0.25	1.7	0.2
L7307	2000	UV Glass	185	400	1	0.05	2.5	0.25	1	0.1
L7820	500	UV Glass	185	400		0.05				