

Fluorescent - Ring Lights

SPECIFICATIONS


LAMP DESCRIPTION
ORDERING CODE

CROSS REFERENCE

MANUFACTURER - LAMP #
EQUIPMENT MODEL #

UFL-FCB74L/CW COOL WHITE
3000125

Watts 6W
Starting Test Voltage 100V
Rated Voltage 50V
Rated Current 0.12A
Color Temperature 4200K
Average Life 2000h
Base G10Q



Diameter (A) 74.0mm
Length (B) 94.5mm
Length (C) 53.0mm

MICROSCOPE - Illuminator
Bausch & Lomb: 31-31-30


Hi-Tech lamps

800-229-6509

info@hi-techlamps.com

UFL-FCB74L/D DAYLIGHT
3000126

Watts 6W
Starting Test Voltage 100V
Rated Voltage 50V
Rated Current 0.12A
Color Temperature 6250K
Average Life 2000h
Base G10Q




Diameter (A) 74.0mm
Length (B) 94.5mm
Length (C) 53.0mm

MICROSCOPE - Illuminator
Bausch & Lomb: 31-31-31

UFL-FCB74L/WW WARM WHITE
3000127

Watts 6W
Starting Test Voltage 100V
Rated Voltage 50V
Rated Current 0.12A
Color Temperature 3000K
Average Life 2000h
Base G10Q




Diameter (A) 74.0mm
Length (B) 94.5mm
Length (C) 53.0mm

MICROSCOPE - Illuminator
Bausch & Lomb: 31-31-30

UFL-FCB80/CW COOL WHITE
3000128


Watts 8W
Starting Test Voltage 100V
Rated Voltage 50V
Rated Current 0.16A
Color Temperature 4200K
Average Life 2000h
Base G10Q



Diameter (A) 80.0mm
Length (B) 112.2mm
Length (C) 63.0mm

UFL-FCB80/D DAYLIGHT
3000129

Watts 8W
Starting Test Voltage 100V
Rated Voltage 50V
Rated Current 0.16A
Color Temperature 6300K
Average Life 2000h
Base G10Q



Diameter (A) 80.0mm
Length (B) 112.2mm
Length (C) 63.0mm

MICROSCOPE - Illuminator
Meiji
Shin Nippon